

ABRASIVES FOR METAL FABRICATION

Get the most demanding jobs done right and done fast.



CUT THROUGH BARRIERS BETWEEN YOU AND YOUR BEST WORK

Introducing Tiger 2.0 — An evolution in abrasives technology. It was designed to be more than just a better product. It was created to help you do your best work.

CUT THROUGH INEFFICIENCY

Tiger 2.0's unique formulation provides the same fast cutting speed, while lasting up to 40% longer. And it's industry first, patent pending optimal use line ensures you get more done with less.

CUT THROUGH SAFETY ISSUES

Tiger 2.0 delivers predictable, smooth cutting and grinding, making the work safer. And it now has a QR code so operators can access crucial safety information right where — and when — they need it.

GUT THROUGH LABOR SHORTAGES

Tiger 2.0 makes cutting and grinding easier, which means operators aren't as worn out at the end of each shift. The unique formulation also produces more consistent work from user to user, reducing training time and even re-work.

3X

Tiger 2.0 cuts through the barriers holding you back from realizing gains while reducing costs. In some cases, users are seeing **3 times more efficiency** over their previous abrasives.





FAST SPEED +

Up to **40% longer wheel life** reduces change-overs and delivers more cuts.



Tiger 2.0



Industry Standard

Advanced 2.0 bond formulation reduces uneven edge wear and chipping, improving user experience and extending wheel life.



INDUSTRY STANDARD

SELECTING THE RIGHT ABRASIVE

Weiler's bonded abrasives help Metal Fabrication professionals get the most demanding jobs done right and done fast. Our high-quality line helps you select the best solution for the toughest jobs. Whether you're working in a shipyard, on a pipeline, or in a fab shop, Weiler will get it done for you.









TIGER® CERAMIC

Self-sharpening and cool – grinds at lower temperatures with less friction and less effort, reducing heat discoloration of the work piece.

GRAIN TYPE

Ceramic alumina

CONTAMINANT FREE

CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE

BEST ON STEEL / METAL

STAINLESS

Hard-to-Grind metals include tool steel, inconel, high nickel alloy, titanium and armored steel

TIGER® PIPELINE

Designed for bead and angle grinding applications on the pipeline.

GRAIN TYPE

Zirconia alumina + ceramic alumina infusion

BEST ON

STEEL / METAL





TIGER

CUT RATE: • • • • LIFE: • • • •

TIGER ZIRC

Self-sharpening grains retain a high cut rate throughout the life of the wheel for exceptional performance.

GRAIN TYPE

Cutting/Combo: Zirconia alumina Grinding: Zirconia alumina + ceramic alumina infusion

CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE

BEST ON

STEEL / METAL

includes structural steel and cast iron

TIGER INOX

Tiger INOX wheels deliver a worry-free solution for stainless steel applications.

GRAIN TYPE

White aluminum oxide

CONTAMINANT FREE

BEST ON

STAINLESS

and harder grade steel



Weiler's non-loading formula delivers a fast and consistent cut rate on aluminum and soft alloys.

GRAIN TYPE

Silicon carbide / aluminum oxide blend

CONTAMINANT FREE CONTAIN LESS THAN 0.1% IRON, SULFUR & CHLORINE

BEST ON

ALUMINUM



PERFORMANCE LONG LIFE

TIGER

CUT RATE: LIFE: • • • • •

TIGER AO

Tiger wheels provide an even, sharp, clean cut and a hard bond extends wheel life.

GRAIN TYPE

Aluminum oxide

BEST ON

STEEL / METAL



VALUE FAST CUT



CUT RATE: • • • • LIFE: • • • • •

WOLVERINE®

Fast cut rate and consistent performance at a good value.

GRAIN TYPE

Aluminum oxide

BEST ON STEEL / METAL







TYPE

Cutting




Type 27 (Depressed Center)




Grinding

Type 28 (Depressed Center)



Designed for increased aggression at lower working angles and increased access

Type 27 (Depressed Center)



Flat profile with depressed center allows for a wide range of grinding angles (0-45)

Type 11 Cup



Type 16 Cone



Type 17 Cone



Type 18 Plug




Grinding Face

Type 18R Plug

GRIT / GRAIN / GRADE

Selecting the best grit, grain and grade combination for your application can increase wheel effectiveness and user productivity. Use the charts below to help pick the right wheel for the job.






Grade (Hardness)



APPLICATION

When selecting a wheel, always choose the thinnest wheel that will perform the cut while maintaining desired product life.



CUTTING WHEELS 500

Weiler's diverse line of cutting wheels provides consistent, well-balanced, high quality solutions. From our 1-millimeter cutting wheels that slice through metal to our large diameter wheels for the biggest cuts, professionals get the most demanding jobs done right and done fast.

FEATURES:

- · Additional fiberglass reinforcement provides added strength for aggressive cutting
- Smooth outer layer reduces friction for an **effortless cut and less kickback** during operation
- Optimum Use Line helps maximize wheel life, improving productivity and sustainability
- 20 Longer wheel life reduces change-overs and delivers more cuts



TYPE 1

7/8" Arbor

UltraCut wheel making precision cuts a steel tube stock.

1MM CUTTING WHEELS





HIGH PERFORMANCE

STEEL/METAL TIGER ZIRC ULTRACUT 1MM / Fast Cut & Long Life

	Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #				
	4-1/2"	1 mm	Z60T	13,300	50	58005				
	5"	1 mm	Z60T	12,200	50	58006				
İ	STAINLESS TIGER INOX ULTRACUT 1MM / Contaminant-free*									
	4-1/2"	1 mm	INOX60T	13.300	50	58130				

INOX60T

12,200

^{*}Contaminant-free (Contains less than 0.1% Fe, S, CI)





MAX PERFORMANCE

STEEL / META	TIGER CE	RAMIC Life & Cut		TYPE 1 7/8" Arbor		TYPE 27 7/8" Arbor		TYPE 27 5/8"-11 Hub	
HARD-TO-CUT							_		
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	.045"	CER60S	13,300	25	58300	25	58305	10	58306
5"	.045"	CER60S	12,200	25	58301	25	58307	10	58308
6"	.045"	CER60S	10,200	25	58302	25	58309	10	58310
7"	.060"	CER60S	8,600	25	58303	25	58311	10	58312

NEW 2.0 BOLD items only.

HIGH P	ERFORM	JANCE		TYF	PE 1	TYP	E 27	TYPE	27
		IAITOL		7/8" Arbor		7/8" Arbor		5/8"-11 Hub	
STEEL / MET	AL TIGER ZI	RC 2.0 / Fas	st Cut & Long I	Life ———					
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	.045"	Z60T	13,300	25	58000	25	58020	10	58030
5"	.045"	Z60T	12,200	25	58001	25	58021	10	58031
6"	.045"	Z60T	10,200	25	58002	25	58022	10	58032
7"	.060"	Z60T	8,600	25	58003	25	58023	10	58033
STAINLESS	TIGER IN	IOX / Conta	minant-free*						
4-1/2"	.045"	INOX60S	13,300	25	58100	25	58110	10	58109
5"	.045"	INOX60S	12,200	25	58101	25	58111	_	_
6"	.045"	INOX60S	10,200	25	58102	25	58112	10	58113
7"	.060"	INOX60S	8,600	25	58103	25	58107	_	_
ALUMINUM	TIGER A	LUMINUM	/ Non-loadin	g / Contam	inant-free*				
4-1/2"	.045"	ALU60S	13,300	25	58200	25	58205	10	58206
5"	.045"	ALU60S	12,200	25	58201	_	-	-	-
6"	.045"	ALU60S	10,200	25	58202	25	58209	10	58210

NEW 2.0 BOLD items only.

PERFORMANCE

TYPE 1 7/8" Arbor

TYPE 27 7/8" Arbor

TYPE 27

7/8" Arbor

TYPE 27 **5/8"-11 Hub**

STEEL/METAL TIGER AO 2.0 / Long Life												
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #			
4-1/2"	.045"	A60T	13,300	25	57020	25	57041	10	57040			
	1/16"	A36T		25	57061	-	_	_	_			
	3/32"	A36S		_	_	25	57081	10	57080			
5"	.045"	A60T	12,200	25	57021	25	57043	10	57042			
	3/32"	A36S		_	_	25	57083	10	57082			
6"	.045"	A60T	10,200	25	57022	25	57045	10	57044			
7"	.060"	A60T	8,600	25	57023	25	57046	10	57048			
9"	1/16"	A60T	6,600	_	_	25	57047	10	57049			

V VALUE

STEEL/METAL WOLVERINE AO / Fast Cutting

ALU60S

8,600

TYPE 1 5/8" Arbor

TYPE 27 5/8" Arbor

TYPE 27

5/8"-11 Hub

	WOLVEIIIVE A	o / Tast Gutting					
Dia.	Thickness	Grade	Max. RPM	Pack	Item #	Pack	Item #
4"	.035"	A60T	15,300	25	56271	_	_
4"	3/32"	A24T	15,200	_	_	25	56474
5"	.035"	A60T	12,200	25	56108	_	_

TYPE 1

7/8" Arbor

VALUE STEEL / METAL

WOLVERINE AO / Fast Cutting								
Thickness	Grade	Max. RPM	Std.					
.045"	A60T	13,300						

Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	.045"	A60T	13,300	25	56281	_	_	_	_
	.045"	A60S		_	_	25	56393	_	_
	1/16"	A60T		25	56103	_	_	_	_
	3/32"	A24T		_	_	25	56475	10	56385
5"	.045"	A60S	12,200	_	_	25	56392	_	_
	1/16"	A36T		25	56118	_	_	_	_
	3/32"	A24T		_	_	25	56476	10	56384
6"	.040"	A60T	10,200	25	56282	_	_	_	_
	.045"	A60T		25	56273	_	_	_	_
	.045"	A60S		_	_	25	56283	_	_
	3/32"	A24R		_	_	25	56277	10	56278
7"	.045"	A60T	8,600	25	56275	_	_	_	_
	.060"	A60S		_	_	25	56391	_	_
	3/32"	A24R		_	_	25	56383	10	56477
9"	1/8"	A24T	6,600	_	_	_	_	10	56423





57040









MAX PERFORMANCE

STEEL / METAL	TIGER° CERAM	IC.		T) (F	NE 4	T)/5		
CTAINI ECC	Superior Life &				PE 1 Arbor	TYPE 1 3/8" Arbor		
	Contaminant-fre			1/4 /	AI DOI			
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	
3"	1/16"	CER36T	25,000	100	58345	100	58342	
4"	1/16"	CER36T	19,000	_	-	25	58348	

*Contaminant-free (Contains less than 0.1% Fe, S, CI)

TYPE 1

HIGH PERFORMANCE

Н	IIGH PER	RFORMAN	CE		TYF		TYPE 1		
\$	STEEL / METAL	TIGER ZIRC /	Fast Cut & Long I	_ife	1/4" /	Arbor	3/8" Arbor		
	Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	
	3"	.035"	Z60T	25,000	100	58012	100	58011	
	4"	.035"	Z60T	19,000	25	58014	25	58013	

TYPE 1





EL / METAL	TIGER AO / Lo	ng Life		1/4" /	Arbor	3/8" Arbor	
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #
2"	.035"	A60T	30,000	100	57014	100	57010
	1/16"	A36T			57015		57011
	1/8"	A36T			57016		57012
3"	.035"	A60T	25,000	100	_	100	57001
	1/16"	A36T			57066		57060
	1/8"	A36T			57068		57063
4"	.035"	A60T	19,000	25	57075	25	57070
	1/16"	A36T			_		57071
	1/8"	A36T			_		57072



VALUE

STEEL / METAL	WOLVERINE® A	AO / Fast Cut			Arbor	3/8" Arbor		
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	
2"	.035"	A60T	30,000	100	56013	100	56128	
	1/16"	A36T		50	56015	50	56129	
	1/8"	A36S		50	56022	50	56130 •	
3"	.035"	A60T	25,000	100	56061	100	56062	
	1/16"	A36T		100	56065	100	56068	
	1/16"	A60T		_	_	100	56070	
	1/8"	A36T		_	_	50	56076	
	1/8"	A36S		50	56060	_	_	
4"	.035"	A60T	19,000	50	56165	50	56080	
	1/16"	A36T		50	56166 •	50	56086	
	1/8"	A36T		_	_	50	56099	



SMALL DIAMETER SNAGGING WHEELS





PER

RFORMANCE	TYPE 1 3/8" Arbor

STEEL / METAL	TIGER AO / Lo	ong Life					
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #
3"	1/4"	A24T	25,000	40	57064	-	-
4"	1/4"	A24T	15,300	10	57073	10	57074



VALUE

OTELET WETAL WOL	VERINE AU / Fast (Jutting		_		
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	
2"	1/4"	A60T	30,000	25	56131	
3"	1/4"	A24T	25,000	25	56064	
Λ"	1///"	V36T	15 300	10	56163	ĺ

TYPE 1
3/8" Arbor

TYPE 27

3/8" Arbor



PERFORMANCE

STEEL / METAL TIGER AO / Long Life

•		I Long Line	,				
Diameter	Thickness	Arbor	Grade	Description	cription Max. RPM Std.		Item #
12"			Long Life Cutting	5,100	10	57090	
14" 3/32" 1" A36T		Long Life Cutting	4,400	10	57092		
14"	3/32"	2" 1" A36R		Smooth Cutting	4,400	10	57093 ◆
14"	3/32"	1"	EA36T	Fast Cut & Long Life	4,400	10	57086
16"	3/32"	1"	A36P	Long Life Cutting	3,850	10	57087

Softer bond for smoother, faster cutting.

TYPE 1

TYPE 1

TYPE 1

TYPE 1

TYPE 1

V VALUE

STEEL / METAL WOLVERINE AO / Fast Cutting

	AAOLALI	IIIVL AU /	ast outling				
Diameter	Thickness	Arbor	Grade	Description	Max. RPM	Std. Pack	Item #
12"	3/32"	1"	A46T	Fast Cutting	5,100	10	56239
14"	14" 3/32" 1" A46T		Fast Cutting	4,400	10	56240	
14"	3/32"	1"	A46T	Single Center Reinforcement For + Speed	4,400	10	56247

FOR HIGH SPEED SAWS



HIGH PERFORMANCE

STEEL/METAL TIGER ZIRC / Fast Cut & Long Life / Rail Cutting

	I I I ULI LI	iii / Tast Gt	it & Long Life	FIGER ZING / Fast out & Long Life / Hair outting											
Diameter	Thickness	Arbor	Grade	Description	Max. RPM	Std. Pack	Item #								
14"	1/8"	1"	Z24U	Rail Cutting	5,500	10	58028								
16"	1/8"	1"	Z24U	Rail Cutting	4.800	10	58029								

PERFORMANCE

STEEL/METAL TIGER AO / Long Life

Diameter	Thickness	Arbor	Grade	Description	Max. RPM	Std. Pack	Item #
12"	1/8"	1"	A30T	Long Life Cutting	6,400	10	57030
14"	1/8"	1"	A30T	Long Life Cutting	5,500	10	57032
14"	1/8"	20 mm	A30T	Long Life Cutting	5,500	10	57094
14"	1/8"	20 mm	A30T	Triple Reinforcement For + Support	5,500	10	57035





PERFORMANCE

FLMIOR	IIVIAIVU	-				TYP	PE 1
STEEL / META	TIGER A) / Long Life)				
Diameter	Thickness	Arbor	Grade	Description	Max. RPM	Std. Pack	Item #
14"	1/8"	1"	A30R	Long Life Cutting	4,400	10	57091
20"	1/8"	1"	A30S	Long Life Cutting	3,100	10	57097

VALUE

STEEL / METAL WOLVERINE AO / Fast Cutting

	TTOLTE	IIIL AO 7	ust outting				
Diameter	Thickness	Arbor	Grade	Description	Max. RPM	Std. Pack	Item #
14"	1/8"	1"	A30R	Fast Cutting	4,400	10	56230



GRINDING WHEELS 0-45°

Whether you're looking for serious stock removal, beveling, grinding, or notching, Weiler's grinding will help get the most demanding jobs done right and done fast.

FEATURES:


- Fiberglass cut back design provides **aggressive grinding right out of the box** (Tiger 27 grinding wheels only)
- Triple fiberglass reinforcement increases user safety
- Optimum Use Line helps maximize wheel life, improving productivity and sustainability
- Longer wheel life reduces change-overs and removes more material
- Advanced 2.0 bond formulation reduces uneven edge wear and chipping, improving operator
 experience and extending wheel life



Weld blending on a stainless pressure tank with a Tiger Ceramic grinding wheel.









NEW 2.0 BOLD items only.

P MAX PERFORMANCE

STEEL / N STAINL HARD-TO-	0 ' 1	CERAMIC ior Life & Cu minant-free	ıt	TYP 5/8" <i>A</i>		TYP 7/8 " <i>I</i>		TYPE 27 5/8"-11 Hub	
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item#
4"	1/4"	CER24R	15,300	10	58335	_	_	_	_
4-1/2"	1/4"	CER24R	13,300	_	_	10	58325	10	58326
5"	1/4"	CER24R	12,200	_	_	10	58327	10	58328
6"	1/4"	CER24R	10,200	_	_	10	58329	10	58330
7"	1/4"	CER24R	8,600	_	_	10	58331	10	58332
9"	1/4"	CER24R	6,600	_	_	10	58333	10	58334

NEW 2.0 BOLD items only.

	PERFOR		Eramic-infused	TYPI 5/8" <i>A</i>		TYPE 7/8" A				
	& Long Life	ZIIIO 7 00	ranne mrasea		_		_		_	
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #	
4"	1/4"	Z24T	15,300	10	58069	_	_		_	
4-1/2"	1/4"	Z24T	13,300	_	_	10	58071	10	58070	
5"	1/4"	Z24T	12,200	_	_	10	58073	10	58072	
6"	1/4"	Z24T	10,200	_	_	10	58079	10	58078	
7"	1/4"	Z24T	8,600	_	_	10	58075	10	58074	
9"	1/4"	Z24T	6,650	_	_	10	68384	10	68385	
STAINL	ESS TIGER	RINOX / C	ontaminant-fre	e*						
4-1/2"	1/4"	INOX24R	13,300		_	10	58121	10	58120	
5"	1/4"	INOX24R	12,200	_	_	10	58123	10	58122	
6"	1/4"	INOX24R	10,200	_	_	10	58129	10	58128	
7"	1/4"	INOX24R	8,600	_	_	10	58125	10	58124	
ALUMIN	TIGER	ALUMINU	JM / Non-loa	ding / Conta	minant-free*					
4-1/2"	1/4"	ALU24R	13,300	_	_	10	58225	10	58226	
5"	1/4"	ALU24R	12,200	_	_	10	58227	10	58228	
6"	1/4"	ALU24R	10.200	_		10	58229	10	58230	

BLACK BOLD ITEM numbers indicate Tiger 2.0. *Contaminant-free (Contains less than 0.1% Fe, S, Cl)

Non-stock product, contact Customer Service for lead times.



PERFORMANCE Di 4-1

TEEL / N	TIGER	RAO / Long	g Life				_		
Dia.	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
4-1/2"	1/4"	A24R	13,300	_	_	10	57121	10	57120
5"	1/4"	A24R	12,200	_	_	10	57123	10	57122
6"	1/4"	A24R	10,200	_	_	10	57129	10	57128
7"	1/4"	A24R	8,600	_	_	10	57125	10	57124
9"	1/4"	A24T	6,650	_	_	10	68376	10	68377

TYPE 27

5/8" Arbor

TYPE 27

7/8" Arbor



BLACK BOLD ITEM numbers indicate Tiger 2.0.

TYPE 27


5/8"-11 Hub

V	VALUE				TYP 5/8" /		TYP 7/8" /	E 27 Arbor	TYP 5/8"-1	
	STEEL / MET/	WOLVER	INE° AO / I	ast Cutting		_	_			
	Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	Std. Pack	Item #
	4"	1/4"	A24R	15,200	25	56473	_	_	_	_
	4-1/2"	1/4"	A24R	13,300	_	_	25	56464	10	56454
	4-1/2"	1/4"	A24N	13,300	_	_	25	56457	10	56455
	5"	1/4"	A24R	12,200	_	_	25	56466	10	56449
	6"	1/4"	A24R	10,200	_	_	25	56280	10	56279
	7"	1/4"	A24R	8,600	_	_	25	56467	10	56468
	9"	1/4"	A24R	6,600	_	_	25	56469 •	10	56470










10

57137

NEW 2.0 BOLD items only.

HIGH PER STEEL / METAL - Fast Cut & Long	TIGER° ZIRC /		TYPE 28 TYPE 28 7/8" Arbor 5/8"-11 Hu				
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #
7"	1/4"	Z24T	8,600	10	58081	10	58080
9"	1/4"	Z24T	6,600	10	58083 •	10	58082



6,600

BLACK BOLD ITEM numbers indicate Tiger 2.0.

57136

10



ACCESSORIES

ADAPTING NUTS & SPANNER WRENCH For 4" - 6" Angle Grinders.

A24R

		Min. Wheel		
Description	Adapts To	Thickness	Standard Pack	Item Number
Adapting Nuts	5/8" to 3/8"-24	.045"	1	56484
Adapting Nuts	7/8" to 5/8"-11	.045"	1	56494
Spanner Wrench	_	_	1	56495



MOUNTING MANDRELS 1/4" Stem. For Type 1 Wheels Only.

Arbor Size	Arbor Size Wheel Thickness Standard Paci		Item Number
1/4"	1/8" to 1/4"	10	56489
3/8"	1/8" to 1/4"	10	56490
1/4". 3/8" *	1/8" to 1/4"	10	56491*



ADAPTER for mounting Large Cutting Wheels onto a 20mm arbor.

For Arbor Hole Size	Adapted Arbor Hole Size	Standard Pack	Item Number	
1"	20mm	10	04455	





COMBO WHEELS 0-45° 190°

Weiler's combination wheels offer flexibility and efficiency when switching between cutting and grinding applications.

FEATURES:

- Optimum Use Line helps maximize wheel life, improving productivity and sustainability
- 20 Longer wheel life reduces change-overs and removes more material



TYPE 27

5/8"-11 Hub

TYPE 27

Back gouging a steel plate with a Tiger combo wheel.

CUT & GRIND COMBO WHEELS 📲





TIGER

TIGER

WOLVERINE

58114

58215

57100

NEW 2.0 BOLD items only.

MAX PERFORMANCE TIGER CERAMIC

	Superior Life & C Contaminant-fre				_			
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #	
4-1/2"	1/8"	CER30T	13,300	25	58315	10	58316	
5"	1/8"	CER30T	12,200	25	58317	10	58318	
6"	1/8"	CER30T	10,200	25	58319	10	58320	
7"	1/8"	CER30T	8,600	25	58321	10	58322	
9"	1/8"	CER30T	6.600	25	58323	10	58324	

TYPE 27

7/8" Arbor

TYPE 27

NEW 2.0 BOLD items only.

P HIGH PERFORMANC	I
-------------------	---


TYPE 27 E TYPE 27 5/8"-11 Hub 7/8" Arbor STEEL / METAL TIGER ZIRC / Fast Cut & Long Life Max. RPM Diameter Thickness Grade Std. Pack Item # Std. Pack Item # 58051 58050 Z301 Z301 25 58053 58052 1/8 Z301 10,200 25 58064 10 58054 58055

9"	1/8"	Z30T	6,650	25	68382	10	68383
STAINLESS	TIGER INOX /	Contaminant-fr	ree*				
4-1/2"	1/8"	INOX30T	13,300	25	58115	10	58114
ALUMINUM	TIGER ALUMIN	NUM / Non-loa	ding / Contam	inant-free*			
4-1/2"	1/8"	ALU30T	13,300	25	58215	10	58216

NEW 2.0 BOLD items only.

PERFORMANCE

7/8" Arbor 5/8"-11 Hub STEEL / METAL TIGER AO / Long Life Std. Pack Max. RPM Std. Pack Diameter **Thickness** Grade Item # Item # 57101 57100 A30S 12,200 1/8 A30S 25 57103 57102 10,200 25 57109 1/8 A30S 10 57108 A30S 8,600 57105 25 57104 1/8 10



V	VALUE STEEL/METAL WOLVERINE AO / Fast Cutting					E 27 Arbor	TYPE 27 5/8"-11 Hub	
	Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #	Std. Pack	Item #
	4-1/2"	1/8"	A24T	13,300	25	56430	10	56429
	5"	1/8"	A24T	12,200	25	56428	10	56427
	7"	1/8"	A24T	8 600	25	56/26	10	56/25

PIPELINE WHEELS






Tiger Pipeline grinding wheels are designed specifically for pipeline applications. Whether grinding a bead, facing the land, prepping transitions, or fabricating in the vard, this wheel is ready to work out of the box, delivering consistent, aggressive grinding throughout the life of the wheel, eliminating the need to chip it.

FEATURES:

- **Do Not Chip** Operators will no longer feel the need to chip the wheel to get it to bite
- **Reduced Chatter** A unique bond formulation delivers reduced vibration for the entire life of the wheel for a better grinding experience
- Superior Life & Cut A blend of zirconia alumina and ceramic grains bite into the bead and dig out the wagon tracks fast while the strong bond delivers long wheel life



One Wheel for





GRINDING NOTCHING



HIGH PERFORMANCE PIPELINE GRINDING WHEELS

STEEL/METAL TIGER ZIRC / Ceramic-infused / Fast Grinding & Long Life on Pipe

Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #				
4-1/2"	1/8"	Z30T	13,300	10	58090				
6"	1/8"	Z30T	10,200	10	58092				
7"	1/8"	Z30T	8,600	10	58094				
9"	1/8"	Z30T	6,600	10	58095				

FOR MECHANIZED PIPE WELDING



Tiger Mech wheels are designed for notching applications on mechanical pipe welds. These high-performance wheels are thinner than standard pipe notching wheels, allowing operators to grind the bead without widening or scarring the bevel.

FEATURES:

- **Designed to Fit** Tiger Mech reaches the bead without widening the bevel
- **Optimized Performance** Designed specifically to grind starts and stops on J and K bevels
- Superior Life & Cut A blend of zirconia alumina and ceramic grains bite into the bead fast while the strong bond delivers long wheel life



HIGH PERFORMANCE MECH NOTCHING WHEELS

STEEL/METAL TIGER ZIRC / Ceramic-infused / Notching Mechanized Pipe Welds

	. Line / coramo ime				
Diameter	Thickness	Grade	Max. RPM	Std. Pack	Item #
4-1/2"	3/32"+	Z30T	13,300	10	58066
7"	3/32"+	730T	8,600	10	58068

+ Specific size for mechanized pipe welds

5/8"-11 Hub

TYPE 27

5/8"-11 Hub



FLARING CUP WHEELS, CONES & PLUGS



Tiger cups, cones, and plugs provide high performance grinding solutions for the toughest materials and the most challenging applications.

Type 11 cup aggressively removing metal.

FEATURES:

- Precision balanced to ensure smooth, vibration free operation and reduced operator fatigue
- Anchored hexagon nut locks the abrasive in place to increase safety and prevent product breakage
- Zinc plated nut prevents oxidation, eliminates contamination, and allows for easy mounting
- Open face design on cones and plugs provides an aggressive cut-rate right out of the box






APPLICATIONS:

Heavy metal removal, grinding, transitioning, rough beveling and removing cracks/flaws

RIM (W) WIDTH OPTIONS

1-1/2" RIM Large grinding zone to minimize grind time						
1" RIM	Medium grinding zone for maximum material removal in targeted areas					
3/4" RIM	Ideal for targeted material removal in small, hard-to-access areas					





68352

HIGH PERFORMANCE STEEL / METAL TIGER ZIRC CUP WHEELS / Fast Cut & Long Life

				3				
Diameter	Thickness	Arbor	Rim	Back		Max.	Std.	
(D / J)	(T)	(H)	(W)	(E)	Grade	RPM	Pack	Item #
4" / 3"	2"	5/8"-11	3/4"	3/4"	ZA160	9,070	5	68352
5" / 3-3/4"	2"	5/8"-11	1"	3/4"	ZA160	7,260	5	68355
6" / 4-3/4"	2"	5/8"-11	1"	3/4"	ZA160	6,000	5	68358
6" / 4-3/4"	2"	5/8"-11	1-1/2"	3/4"	ZAC16Q	6,000	5	68361+
C" / 4 0 / 4"	2"	E /O" 11	1 1 / 0 !!	0/4"	7 A 1 C D	C 000	Г	cooco

^{3/4&}quot; ZA160 6,000 5 68364

+ Includes silicon carbide for burnt-in sand and hard-to-grind metals



8356



PERFORMANCE

STEEL/METAL TIGER AO CUP WHEELS / Long Life										
Diameter	Thickness	Arbor	Rim	Back		Max.	Std.			
(D / J)	(T)	(H)	(W)	(E)	Grade	RPM	Pack	Item #		
4" / 3"	2"	5/8"-11	3/4"	3/4"	A16Q	9,070	5	68350 •		
5" / 3-3/4"	2"	5/8"-11	1"	3/4"	A16Q	7,260	5	68353		
6" / 4-3/4"	2"	5/8"-11	1"	3/4"*	A16Q	6,000	5	68356		
6" / 4-3/4"	2"	5/8"-11	1-1/2"	3/4"*	A160	6,000	5	68359		
							*D-:			

*Reinforced metal back

CUP WHEEL MOUNTING FLANGE - Fits over 5/8"-11 spindles

Diameter	Thickness	Std. Pack	Item #
2"	1/4"	1	73054 •

• Non-stock product, contact Customer Service for lead times.

CONES AND PLUGS

FOR STRAIGHT & DIE GRINDERS

APPLICATIONS:

ID cleaning, hole edge beveling, smoothing weld seams, removing parting lines and cleaning castings in hard-to-reach places

TYPE 16 CONES

HIGH PERFORMANCE STEEL/METAL TIGER ZIRC TYPE 16 CONES / Fast Cut & Long Life

Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #		
1"	3"	3/8"-24 Nut	ZA20S	36,290	12	68301		
1-1/2"	2-1/2"	5/8"-11 Nut	ZA20S	24,190	12	68304		
1-1/2"	2"	3/8"-24 Nut	ZA20S	24,190	12	68306		
1-1/2"	3"	5/8"-11 Nut	ZA20S	24,190	12	68308		
2"	3"	5/8"-11 Nut	ZA20S	18,145	12	68311		
2-3/4"	3-1/2"	5/8"-11 Nut	ZA20S	13,195	12	68313		





PERFORMANCE STEEL/METAL TIGER AO / Long Life

Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #
1-1/2"	2-1/2"	5/8"-11 Nut	A24R	24,190	12	68303
1-1/2"	3"	3/8"-24 Nut	A24R	24,190	12	68305
1-1/2"	3"	5/8"-11 Nut	A24R	24,190	12	68307
2"	3"	3/8"-24 Nut	A24R	18,145	12	68309
2"	3"	5/8"-11 Nut	A24R	18,145	12	68310
2-3/4"	3"	5/8"-11 Nut	A24R	13,195	12	68312
3"	3"	5/8"-11 Nut	A24R	12,100	12	68314 •



HIGH PERFORMANCE STEEL/METAL TIGER ZIRC TYPE 17 CONES / Fast Cut & Long Life

Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #
2"	3"	5/8"-11 Nut	ZA20S	18,145	12	68365



PERFORMANCE STEEL/METAL TIGER AO / Long Life

Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #
1-3/4"	3"	5/8"-11 Nut	A24R	20,740	12	68316
2"	3"	5/8"-11 Nut	A24R	18,145	12	68317



HIGH PFRFORMANCE STEEL/METAL TIGER ZIRC TYPE 18 PLUGS / Fast Cut & Long Life

IIIOII I LII	TIGEN ZING TIFE TO FLOGS / Tast out & Long Life									
Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #				
1-1/2"	2-1/2"	5/8"-11 Nut	ZA20S	24,190	12	68320				
1-1/2"	3"	5/8"-11 Nut	ZA20S	24,190	12	68322				
2"	3"	5/8"-11 Nut	ZA20S	18,145	12	68324				





PERFORMANCE STEEL/METAL TIGER AO / Long Life

TIGEN AO 7 LONG LINE									
Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #			
1-1/2"	2-1/2"	3/8"-24 Nut	A24R	24,190	12	68318			
1-1/2"	2-1/2"	5/8"-11 Nut	A24R	24,190	12	68319			
1-1/2"	3"	5/8"-11 Nut	A24R	24,190	12	68321			
2"	3"	5/8"-11 Nut	A24R	18,145	12	68323			



TYPE 18R PLUGS

HIGH PERFORMANCE STEEL/METAL TIGER ZIRC TYPE 18R PLUGS / Fast Cut & Long Life


Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #
1-1/2"	3"	3/8"-24 Nut	ZA20S	24,190	12	68326 •
1-1/2"	3"	5/8"-11 Nut	ZA20S	24,190	12	68328
2"	3"	5/8"-11 Nut	ZA20S	18,145	12	68330





PERFORMANCE STEEL/METAL TIGER AO / Long Life

	.,	ridentito / Long Eno				
Diameter (D)	Thickness (T)	Arbor (Thread)	Grade	Max. RPM	Std. Pack	Item #
1-1/2"	3"	5/8"-11 Nut	A24R	24,190	12	68327
2"	3"	5/8"-11 Nut	A24R	18,145	12	68329
3"	3"	5/8"-11 Nut	A24R	12,100	12	68331



For the full offering of Weiler products, please refer to our Full Line Catalog or visit our website. To discuss specific requirements with a product specialist, call 800.835.9999.

WEILER ABRASIVES GROUP

Weiler Global HQ One Weiler Drive Cresco, PA 18326 USA

Weiler de México Querétaro, México

Weiler do Brasil São Paulo, Brazil Weiler EMEA HQ Maribor, Slovenia

Zreče, Slovenia

Loče, Slovenia

Oplotnica, Slovenia

Bindlach, Germany

